

# CS 60 | WIRE STRIPPER



## Abisolieren von Kabeln und Litzen

Die elektrische Abisoliermaschine **CS 60** ist einfach und intuitiv zu bedienen. Das übersichtliche Display visualisiert die eingegebenen Werte. Querschnitt und Abisolierlänge sind in wenigen Sekunden eingestellt, dadurch ist der **CS 60** auch für kleinere Serien bestens geeignet. Die kurze Einfühlrlänge und der einsehbare Arbeitsbereich ermöglichen schnelles und ermüdungsfreies Arbeiten. Die Klemmkraft wird automatisch dem Kabelquerschnitt angepasst. So entstehen keine Druckstellen auf empfindlichen Isolationen.

### Optionen

- Form-, Radius- und Parallelmesser für Sonderkabel
- Diamantbeschichtete Klemmbacken für sehr harte Isolationen

- ☞ Einfache, intuitive Bedienung
- ☞ Querschnittsbereich: 0.08-6 mm<sup>2</sup>
- ☞ Schnelle Zykluszeit
- ☞ Voll- und Teilabzug
- ☞ Automatische Anpassung der Klemmkraft
- ☞ Kompakt und mobil, mit Tragegriff
- ☞ V-Messer für alle gängigen Kabeltypen

## Stripping of cables and strands

The **CS 60** electric wire stripper is easy and intuitive to operate. The entered values are clearly visualised on the display. The cross-section and stripping length can be adjusted in seconds, making the **CS60** ideal for small series applications. The short insertion length and visible working area enable fast and fatigue-free working. The clamping force is automatically adapted to the cable cross-section. This avoids pressure points on sensitive areas of the insulation.

### Options

- Shaped, radius and parallel blades for special cables
- Diamond-coated clamping jaws for very hard insulation materials

- ☞ Simple, intuitive operation
- ☞ Cross-section range: 0.08-6 mm<sup>2</sup>
- ☞ Fast cycle time
- ☞ Full and partial extraction
- ☞ Automatic clamping force adjustment
- ☞ Compact and mobile, with carrying handle
- ☞ V-blade for all common cable types

### TECHNISCHE DATEN:

Querschnitt:	0.08-6 mm <sup>2</sup> (AWG 28-10)
Max. Kabeldurchmesser:	6 mm
Abisolierlänge:	2-20 mm
Teilabzugslänge:	2-20 mm
Einfühlrlänge plus Abisolierlänge:	15 mm + X
Zykluszeit (Vollabzug):	0.3 s
Abisoliermesser:	V-Form
Netzanschluss:	230 VAC/50 Hz
Maße (LxBxH):	363 x 141 x 222 mm
Gewicht:	9.5 kg

### TECHNICAL DATA:

Cross-section:	0.08-6 mm <sup>2</sup> (AWG 28-10)
Max. cable diameter:	6 mm
Stripping length:	2-20 mm
Partial stripping length:	2-20 mm
Feed-in length plus stripping length:	15 mm + X
Cycle time (full strip):	0.3 sec
Stripping blade:	V-shaped
Power supply:	115 VAC/60 Hz
Dimensions (LxWxH):	363 x 141 x 222 mm
Weight:	21 lbs.



Abisoliermesser parallel/Stripping knife parallel



Abisoliermesser Sonder/Stripping knife special

